



# Armario de refrigeración Euronorm 600 x 400



Serie **NACIONAL 400/900L** Series

## CARACTERÍSTICAS TÉCNICAS



### Nuevo controlador digital

El **nuevo controlador** de fácil manejo tiene una mayor precisión en el control de la temperatura. Mayor facilidad para el ajuste del intervalo de temperaturas que deseamos conseguir.



### Iluminación

Incorporación de **iluminación LED**, llegando a **reducir** el consumo energético **entre un 80% y 90%**, respecto a una bombilla tradicional.

## TECHNICAL CHARACTERISTICS

### New control system

Greater precision in temperature control with the **new digital controller**. Easier to adjust the temperature range we want to achieve.

### Lighting

**LED lighting** incorporated, **reducing** energetic consumption **between 80% and 90%** respect to a traditional lighth bulb.

AN 401 T/F



### Controlador digital táctil e intuitivo IP 65.

Digital control easy and intuitive-touch screen IP65 protection.

Más detalles y ficha técnica en:




Versión español

More details and technical sheet:



English version



AN 401 T/F

### MOD.

	Acero inox Stainless Steel [EXT/INT]	Espesor Thickness [MM]	Capacidad Capacity [L]	Puertas Doors	Nº parrillas J. guías No shelves / Slides	Potencia Power [W]	Potencia frigorífica Cooling capacity [W A -10°C]	Consumo Consumption [kWh/24h]	Clase energética Energy class	Refrigerante Refrigerant
AN 401 T/F	AISI 304	55	395	1	3/3 [600x400]	230	343	1,55	<b>C</b>	<b>R-290</b>
AN 902 T/F	AISI 304	55	895	2	6/6 [600x400]	420	690	1,90	<b>B</b>	<b>R-290</b>
AN 904 T/F	AISI 304	55	895	4	6/6 [600x400]	420	690	1,90	<b>B</b>	<b>R-290</b>

Fotografías no contractuales / Non contractual pictures.

Características técnicas y constructivas sujetas a variación sin previo aviso / We reserve the right to change specifications without prior notice.

Los datos técnicos están sujetos a posibles variaciones que serán actualizadas periódicamente en las fichas técnicas del producto, disponibles en la web. The technical data are subject to possible variations that will be updated periodically in the technical data sheets of the product, which are available on the website.



# Euronorm 600 x 400 reach in refrigerator

Serie  
**NACIONAL**  
400/900L  
Series

## REFRIGERACIÓN



### Refrigeración

Sistema de **frío ventilado**.

**Bandeja evaporativa** sin resistencia eléctrica para una mayor eficiencia energética.

## REFRIGERATION

### Refrigeration

**Ventilated cooling** system.

**Evaporative tray** without electrical heater for a better energy class.

AN 904 T/F



AN 401 T/F

557 x 775 x 2060 mm.  
Temp. -2°C/+8°C  
C. Clima. 5 / 40°C  
230V/1ph/50Hz



AN 902 T/F

1124 x 775 x 2060 mm.  
Temp. -2°C/+8°C  
C. Clima. 5 / 40°C  
230V/1ph/50Hz



AN 904 T/F

1124 x 775 x 2060 mm.  
Temp. -2°C/+8°C  
C. Clima. 5 / 40°C  
230V/1ph/50Hz

### Opcional / Optional

Parrilla / Wire shelf [502X26]	<b>39 €</b>
Juego de guías / Slides [GUIA503X04; GUIA503X24]	<b>34 €</b>
Cerradura / Lock [506X209; 506X210]	<b>34 €</b>
Manejo control digital por bluetooth / Operating digital control by bluetooth	<b>122 €</b>
115V/1ph/60Hz	<b>+6%</b>
230V/1ph/60Hz	<b>+3%</b>

